

E600

Casement | Project-Out | Project In | Fixed





Frame Depth 3 1/4"



Rating Casement: Project-Out/In: Fixed:

AW70 AW100 AW100



Design Pressure Casement: 70 Project-Out: 100 Project In: 100 Fixed: 100	U-Value* Casement: .2639 Project-Out: .2637 Project In: .1337 Fixed: .1731
Air Infiltration Casement: <.10 Project-Out: <.10 Project In: <.10 Fixed: <.10	SHGC* Casement: .1041 Project-Out: .1041 Project In: .1041 Fixed: .1355
Water Resistance Casement: 12 Project-Out: 15 Project In: 15 Fixed: 15	* CR* Casement: 43 - 61 Project-Out: 45 - 61 Project In: 44 - 63 Fixed: 44 - 63
OITC×))) Casement: 25 - 34 Other models: Contact Quaker	STC [×]))) Casement: 31 - 42 Other models: Contact Quaker

FEATURES:

- ► Architectural grade aluminum frame
- ► Thermally-broken frame and sash with pourand-debridge technology
- ► 3 ⁹/₁₆" narrow sitelines
- ▶ 1" insulating glass
- ► Roto or Cam Handle hardware
- ► Standard High-Performance 2604 Powder Paint Finish (an FGIA Specification)
- ► Optional Upgrade to 2605 Powder Paint Finish (an FGIA Specification)
- Casement, Project-Out and Project-In operating models
- ► 30+ "Quick-Pick" colors, with unlimited custom colors available.
- ► Impact rated Fixed model (E700 Series)

*-Ranges based on multiple Low-E/Argon I.G. combinations


^x-Ranges based on multiple I.G. combinations



E600


Casement Roto (AW70)

Test size = 36" x 60"




Casement Cam Handle (AW70)

Test size = 36" x 60"




Casement Project In (AW100)

Test size = 36" x 60"




Project-Out Roto (AW100)

Test size = 60" x 36"




Project-Out Cam Handle (AW100)

Test size = 60" x 36"



Fixed (AW100)

Test size = 72" x 120"



All ratings listed are NAFS certified.



QuakerCommercialWindows.com 1-800-347-0438 Commercial@quakerwindows.com